

Company Name: _____ Dept: _____ Location: _____ Date: _____

#100

Floor Openings & Holes

Every floor and roof opening shall be guarded by a cover, a guardrail, or equivalent on all open sides. While the cover is not in place, the openings shall be constantly attended by someone or shall be protected by guardrails. Toeboards shall be installed around the edges at openings where persons may pass below the opening.

1. Floor and roof openings:
 - a. Floor, roof and skylights openings in any work surface must be guarded by railings and toeboards or by covers.
 - b. The cover must be able to support 400 lbs. or twice the weight of the employees, equipment, and material, and be securely fastened.
 - c. Covers must bear a sign with minimum 1 in. letters stating-OPENING-DO NOT REMOVE.
 - d. Employees within 6 ft. of any skylight shall be protected from falling through the skylight opening by any one of the following methods:
 01. Guardrails
 02. Skylight Screens
 03. Personal fall protection system.
 04. Covers installed over the skylights.
 05. Fall protection plan.
EXCEPTION: When the work is of short duration and exposure is limited.
 - e. Access to surfaces glazed with transparent or translucent materials are not permitted unless an engineer certifies that the surface will sustain all anticipated loads.

Meeting Conducted By:

Print Name

Signature

Meeting Attended By:

Document Filing Reference

Notes & Suggestions